

Electric & Propane Foggers

Our Heavy Duty Model 982 Thermo Fogger is designed for multiple commercial applications.

Effectively controls flying insects with oil-based insecticides or odors caused by fire, smoke, pets, mildew, etc. with oil-based deodorant.

With barrel removed, the model 982 turns into an all-purpose electric applicator for applying water-based or oil-based material.

- Heavy-duty, 96-oz. spun-aluminum container
- Thermostatically controlled heating chamber
- Converts 1 oz. of oil-based insecticide into 2,000 cu.ft. of fog in just 2 minutes
- Flow rate adjustable knob
- Heating element easily removed to create a 2 oz./minute all-purpose applicator
- Available in 110 or 220 volts
- NOT RECOMMENDED FOR INDOOR USE

Our Model 960 Electric Fogger offers dependable operations at an economical price. It can be used in many of the same applications as the "982".

- UL listed and available in 110 or 220 volts
- Adjustable for wet or dry fog
- Complete with unbreakable 40-oz. insecticide container
- 1 oz. insecticide creates 2,000 cu. ft. of fog in just 2 minutes
- Includes 1 quart of fogging insecticide
- Touch trigger
- NOT RECOMMENDED FOR INDOOR USE

Our Propane Fogger is completely portable, making it convenient for many outdoor applications, especially when electric outlets aren't available.

- Unbreakable 40-oz. insecticide container
- Trigger lock prevents accidental dispensing of insecticide
- Uses standard propane cylinder (not included)
- Model 1443 includes 1 quart of fogging insecticide packed with the fogger
- NOT RECOMMENDED FOR INDOOR USE



Insect Fog with Synthetic Pyrethrin

- EPA registered insecticide for application through all types of thermal foggers
- Non-persistent low toxicity synthetic pyrethroid with superior knockdown and kill
- Available in 1-quart, 1/2-gallon and 1-gallon sizes in nonbreakable plastic containers



Order Code	Model	Useable Capacity	Qty.	Wt. lbs.	Cubic ea.
982150	982 (110V)	3 qt.	3/case	20.50	3.0
982250	982 (220V)	3 qt.	3/case	20.50	3.0
960110	960 (110V)	40 oz.	3/case w/fog	17.75	3.0
958560	958 (220V)	40 oz.	3/case	17.75	3.0
443652	1443	40 oz.	3/case w/fog	17.75	3.0
100111	F100	1 gal.	6/case	45.00	1.6
100711	F100	.5 gal.	6/case	22.50	.86
100611	F100	1 qt.	12/case	24.00	.98