

# ROYAL ULV (SS)

## **Special Features:-**

- ✓ Faster & Safer
- ✓ Highly Effective infection control
- ✓ An ideal tool for Fumigation, Generate ultrafine & Non-wetting aerosols
- ✓ Specially designed with extreme care for health care & pharmaceutical industries
- ✓ The large no. of very small droplets create high density fog
- ✓ Intake air filter prevents entry of dust for safety of motors parts.
- ✓ Easy to clean, detachable chemical resistance high grade 304 SS tank.



## **Technical Specification:**

1. Power Supply	:	220V AC, 50Hz
2. Motor	:	28000 RPM, the high power (Two Stages Blower Provided)
3. Particle Size	:	5-15 Micron (Maximum Thrust
4. Speed & Reach	:	30-40 Ft. Distance & 18-20 Ft. Height
5. Space Treatment	:	Approx. 8000 cu.ft. (20'x20'x20')
6. Nozzle Assembly	:	Non Rotating Plastic Engine
7. Chemical Tank	:	5 Liter Stainless Steel Gr. 304 (Autoclavable)
8. Machine Handle	:	SS 304 Grade.
9. Liquid Discharge Rate	:	Approx. 0-100 ml/min, adjustable by rotating knob
10. Chemical Tank Cover	:	SS 304 Grade
11. Machine Weight	:	Portable Approx. 6.5 Kg

Manufactured & Marketed by:

## **ROYAL TRADELINKS PVT LTD.**

Regd. Office:- 346, Street No. 4, Govindpuri, New Delhi-110019

Contact Nos.- 011-26472104, 41092226.

Email ID :- [info@foggingmachines.com](mailto:info@foggingmachines.com), [royal@foggingmachines.com](mailto:royal@foggingmachines.com)