

Thermal Fogger
RPF-5
Portable



Technical data:

Weight empty:	7.5 kg
Size (length x breadth x height):	106 x 29 x 33 cm
Capacity of solution tank:	5 litres
Capacity of fuel tank:	2 litres
Cubic capacity of engine:	300 cm ³
Max. performance of engine:	12 kW (16 h.p., 10.318 kcal/h)
Max. fuel consumption:	1,5 l/h
Automatic ignition:	Electronic ignition coil fed by Battery(ies)
Starting device:	Manual start
Flow rate:	10 - 20 l/h (according to nozzle size used)
Standard flow rate:	10 l/h
Droplet size spectrum (depending on oil viscosity and nozzle size used):	< 20 µm (oil) < 60 µm (oil/water) < 100 µm (water)

Fogging technique and application:

Thermal fogging is the generation of ultra-fine droplets in a range of 1-50 µm using thermo-pneumatic energy. Liquid substances are vaporized in the unit and form ultra-fine aerosols by condensing on contact with cool ambient air. Thermal fogging is used for any pest control task where active substances should be uniformly distributed even in inaccessible places, without leaving undesirable residues.

The fogging technique is the solution for treating large areas and spaces with a minimum quantity of pesticide solution, less operational work and with little harm to the environment (less residues, no penetration into the ground), e.g. in the field of public health, stock protection, plant protection, disinfection, decontamination, deodorization and cinema effects.

Subject to technical changes 11/2009

In Technical Collaboration with pulsFOG Dr. Stahl & Sohn GmbH., Germany